

ENBLOC CLEAN LED SMOOTH

- Built-in luminaire designed to cleanrooms.
- Highly efficient LED light source.
- High protection level against dust and water infiltration IP54 or IP65.
- Quick and easy assembly.
- Luminaire lighting surface with a unique visual effect.

ENBLOC CLEAN LED SMOOTH

Features

Luminaire designed for modular and gypsum and plasterboard suspended ceilings, equipped with the highly efficient LED panels. The lighting level of LED sources is 2700 lm, 5400 lm or 10800 lm. Luminaire available in two configurations depending on the color temperature of the light source – 3000 K or 4000 K. Luminaire case made from steel sheet, powder coated in white. Available diffusers: tempered matt glass, PMMA opal diffuser, micro-prismatic diffuser with hardened glass or micro-prismatic diffuser.

Luminaire recommended for: cleanrooms.











ENBLOC CLEAN LED SMOOTH MICRO-PRM

ENBLOC CLEAN LED SMOOTH

ENBLOC CLEAN LED SMOOTH














Dimensions



Φ [lm]	A (mm)	B (mm)	H (mm)	L1xL2
2700	596	296	76	580x280
5400	596	596	76	580x580
5400	1196	296	76	1180x280
10800	1196	596	76	1180x580



ENBLOC CLEAN LED SMOOTH Available colour of the light: 830/840

ENBLOC CLEAN LED SMOOTH ENBLOC CLEAN LED SMOOTH

SDCM=5

Lifetime of LED sources - 50000 h (L70/B50)

Operating temperature range: 5° C - 30° C

The power shown refers to the whole system (tolerance +/- 10%).

19 W 36 W 71 W

LED LED

2700 5400

10800

The given luminous flux refers to LED light sources (tolerance +/- 10% depends on the value of the colour temperature).

Luminaire options

Diffuser:

SHM tempered matt glass

Micro-PRM SH micro-prismatic diffuser with hardened glass

Micro-PRM micro-prismatic diffuser

Control gear:

Е EDD DIM DALI driver

Accessories

Holder - plasterboard ceiling

Luminaire	Index	EAN
Enbloc Clean : T5 L/ED / LED Smooth Enbloc Clean LED CRI90	2M-X414LKPIPT5	5902107117207

Luminaires with the GK mark or U in the name contain plasterboard ceiling holders in the set.

WARNING! Technical data may be changed. Photos of the luminaries may differ from reality. Last updated 01.02.2017. Other options of the luminaire available on request.